

Grease Meter and High Pressure Greasing Accessories

Description

Images and specifications can be subject to change without notice

Part No.

DIGIMET E5 Grease Meter

High pressure digital meter suitable for grease up to NLGI 2, displays dispense volume in ccm, resettable, totaliser in litre, inlet thread R1/4"female.

Working Pressure: max. 500 bar (7.250 psi)
 Burst Pressure: min. 1.000 bar (14.450 psi)
 Accuracy: +/- 3%
 Max. permissible delivery: 2.000 ccm/min.

Digimet E5 without accessories R1/8" **35 415 52**
 Digimet E5 with rigid tube R1/8" **35 415 76**
 Digimet E5 with high pressure rubber hose R1/8" **35 415 90**

Digimet E5 with High Pressure Rubber Hose R1/8"

High pressure digital meter for grease up to NLGI 2, technical data as described above, except for inlet R1/8" is female

DIGIMET E5 inline grease meter **35 415 45**

High Pressure Grease Control Valve, standard

High pressure grease control valve, standard

**Burst pressure max. 450 bar (6.525 psi),
 not suitable for pneuMATO 75**

High pressure grease control valve with straight swivel **34 108 03**
 High pressure grease control valve with straight Z` swivel **34 108 34**

High Pressure Grease Control Valve, deluxe

Robust construction with straight swivel, delivery tube E4024 R1/8", 4-jaw hydraulic coupler, inlet thread 1/4"female, **working pressure max. 600 bar (8.700 psi)**
 Easy operation, without effort, even at high grease pressures.
 Ergonomic plastic hand grip with protective cover, pressure parts in steel, operating trigger with leak proof feature.

High pressure grease control valve, deluxe with rigid tube E4024 **34 108 58**

Straight Swivel for Grease Control Valve

Straight swivel for grease control valve **34 109 02**

Z` Swivel for Grease Control Valve

Heavy duty, ball bearing, R1/4"

Heavy duty with ball bearing, inlet thread R1/4" **34 109 40**

