

Grease Spray Equipment and Accessories

Description	Images and specifications can be subject to change without notice	Part No.
-------------	---	----------

pneuMATO 55 - LubeJet, static

A grease spray system using unique technology: it combines the high pressure lubrication pump pneuMATO 55, with **especially designed spraying equipment**.

The spray pistol has been designed for greases up to NLGI 2, the special "Twin Hose" for grease and high pressure air supply is integrated in a high quality protective sheath.

This sophisticated grease spray system can be fitted to grease pails and drums.

Specification:

pneuMATO 55 -pneumatic pump unit, pressure ratio 1:55, 10m special twin delivery hose, spray gun, pressure regulator 5 bar, **air inlet pressure limited to 5 bar**

version with 3,5 or 6,5 m hose length upon request

pneuMATO 55 - LubeJet, static, for 25 kg, inner-Ø 300-335 mm	33 727 29
pneuMATO 55 - LubeJet, static, for 50 kg, inner-Ø 355-387 mm	33 757 20
pneuMATO 55 - LubeJet, static, for 200 kg, inner-Ø 550-590 mm	33 701 21

pneuMATO 55 - LubeJet, mobile

Item as described above, but mounted to a trolley to carry pails up to 50 kg or drums up to 180 kg

version with 3,5 or 6,5 m hose length upon request

pneuMATO 55 - LubeJet, mobile, for 25 kg, inner-Ø 300-335 mm	33 726 20
pneuMATO 55 - LubeJet, mobile, for 50 kg, inner-Ø 355-387 mm	33 756 21
pneuMATO 55 - LubeJet, mobile, for 200 kg, inner-Ø 550-590 mm	33 700 08

Grease Spray Gun

This spray gun has been specially designed to spray grease. Spray patterns, air and grease volumes are individually adjustable.

Maximum permitted air input pressure is 10 bar (145 psi)
Maximum permitted material pressure is 250 bar (3.625 psi)

Grease spray gun LubeJet	33 793 60
--------------------------	------------------

Spray Lance for pneuMATO 55 - LubeJet

Spray lance with 2-segment extension tube, designed to cover and spread grease in inaccessible spots or cavities. The unit is suitable for common greases up to NLGI-class 2.

Spray lance 2,0 m for pneuMATO 55 - LubeJet	33 795 82
---	------------------

Twin Hose for pneuMATO 55 - LubeJet

This special "Twin Hose" includes high pressure grease supply hose (burst pressure: 1.650 bar, with steel wire reinforcement) and air supply hose. Both hoses are encased in hard wearing outer sheath, which has integral spiral, steel reinforcement.

pneuMATO 55 - LubeJet twin hose system 3,5 m	33 793 08
pneuMATO 55 - LubeJet twin hose system 6,5 m	33 793 15
pneuMATO 55 - LubeJet twin hose system 10 m	33 793 22

Air Pressure Limiter for pneuMATO 55 Lubejet

This air pressure limiter restricts the air supply pressure at the pump inlet to 5 bar. It is supplied with connection for the air supply pipework.

Air pressure regulator for pneuMATO 55 Lubejet	33 794 90
--	------------------

