

High Pressure Lubrication Equipment, Manually Operated

Description

Images and specifications can be subject to change without notice

Part No.

High Pressure Lubricator Bucket Greaser

Pail mounted high pressure manual lubricator, suction tube Ø 40 mm, equipped with 2.0m high pressure safety rubber hose and 4-jaw hydraulic coupler, pail lid - S with 3 thumb screws, and follower plate.

Working pressure : 400 bar (5.800 psi), output 1,6 ccm per stroke.

Suitable for Grease NLGI 000 - 2

Bucket Greaser BG 5-s f. 5 kg,	inner-Ø165-200 mm	33 805 71
Bucket Greaser BG 10-s f. 10 kg,	inner-Ø215-230 mm	33 810 80
Bucket Greaser BG 15-s f. 15 kg,	inner-Ø255-282 mm	33 815 92
Bucket Greaser BG 20-s f. 18/20 kg,	inner-Ø265-285 mm *	33 818 82
Bucket Greaser BG 20-s f. 18/20 kg,	inner-Ø285-305 mm	33 818 37
Bucket Greaser BG 25-s f. 25 kg,	inner-Ø300-335 mm	33 825 82
Bucket Greaser BG 50-s f. 50 kg,	inner-Ø355-387 mm	33 851 70

High Pressure Lubricator Bucket Greaser

for 18/20 kg JOKEY plastic pail

Item as described above, includes self-centering pail lid with special claws to fit and secure grip on the JOKEY pail (Jet 2000).

Bucket Greaser BG 20-d for 18/20 kg JOKEY plastic pail	33 819 50
--	------------------

Foot operated grease pump FP-06 economy

Budget priced foot operated pump with 2,0 m high pressure rubber safety hose and 4-jaw hydraulic coupler, carry handle.

Suitable for Grease NLGI 000 - 2

Maximum working pressure:	up to 500 bar (7.250 psi)
Reservoir capacity:	approx. 6.000 ccm
Output per stroke:	approx. 2 ccm

Foot operated grease pump	FP-06 economy	33 860 09
---------------------------	---------------	------------------

Foot Operated Grease Pump FP-08-heavy duty

Mobile foot operated greaser, equipped with 2,0 m high pressure rubber safety hose and hand control with rigid tube and 4-jaw hydraulic coupler. Additional hand operated pump to pre-charge grease container (follower plate) with air pressure up to 3 bar.

Suitable for Grease up to NLGI 3

Grease pressure:	up to 400 bar (5.800 psi)
Reservoir capacity:	approx. 6.500 ccm
Output per stroke:	approx. 2 ccm

Foot operated grease pump	FP-08-heavy duty	33 860 54
---------------------------	------------------	------------------

High Pressure Hand Control for FP-08

with rigid tube and 4-jaw hydraulic coupler

Hand control with rigid tube for FP-08	33 902 80
--	------------------

